

# PROFESSIONAL REFRIGERATION FOR THE PERFECT KITCHEN



*Elanpro's world class equipment has been developed over decades of painstakingly collected market research and customer experience. Our Freezers and Refrigerators come with high quality components from Europe and are known for reliability and performance. They are designed to work under tough Indian conditions. Elanpro machines can be found in Best Hotels, Bars, Restaurants, Pubs, Cafe's and QSR Chains.*



CGN 3100 C / EGN 3100 C/F  
UC 1801 C / UC 1802 C

- Kitchen Solution • Bar Solution • Confectionery Solution • Ice Machine Solution • Room Solution
- Special Products Solution • Retail Solution • Supermarket Solution

# Kitchen Refrigeration - Reach-in & Counters - Static & Frost Free



CGN 1200 C4/F4, EGN 1410 C4/F4  
CGN 1200 CF, RI 1101 C4/F4

### Key Features:

- Dixell digital controller
- Removable gasket
- Adjustable shelves
- Heavy duty lockable castors
- Lock
- Built in handle
- Environment Friendly Refrigerant
  - R134A for Chillers
  - R404A for Freezers

### Optional Features:

- Left or Right hinged door
- Single or multi door
- Heavy duty adjustable SS legs
- Left or Right side compressor
- Door or drawer options
- Back splash

### Common - All Models

- HACCP Compliance
- Adjustable Feet



CGN 600 C2/F2  
EGN 650 C2/F2  
CGN 600 CF  
RI 551 C2/F2



CGN 2100 C / EGN 2100 C/F  
UC 1501 C / UC 1502 C



Choice of Top & Drawers

	Model	Description	Capacity (Ltrs)	Dimension (WxDxH) mm	Temperature Range	GN Compatibility	No. of Shelves	Climate Class	Inside/ Outside SS
FROST FREE - PREMIUM	EGN 650 C2	2 Door Reach-in Chiller	650	740 x 830 x 2010	-2°C ~ 8°C	2 x GN 1/1	3	43°C	SS 304
	EGN 650 F2	2 Door Reach-in Freezer	650	740 x 830 x 2010	-16°C ~ -22°C	2 x GN 1/1	3	38°C	SS 304
	EGN 1410 C4	4 Door Reach-In Chiller	1410	1480 x 830 x 2010	-2°C ~ 8°C	2 x GN 1/1	6	43°C	SS 304
	EGN 1410 F4	4 Door Reach-in Freezer	1410	1480 x 830 x 2010	-16°C ~ -22°C	2 x GN 1/1	6	38°C	SS 304
	EGN 2100 C	2 Door Under Counter Chiller	265	1360 x 700 x 860	-2°C ~ 8°C	1 x GN 1/1	2	38°C	SS 304
	EGN 3100 C	3 Door Under Counter Chiller	400	1795 x 700 x 860	-2°C ~ 8°C	1 x GN 1/1	3	38°C	SS 304
FROST FREE - CLASSIC	EGN 2100 F	2 Door Under Counter Freezer	265	1360 x 700 x 860	-16°C ~ -22°C	1 x GN 1/1	2	38°C	SS 304
	EGN 3100 F	3 Door Under Counter Freezer	400	1795 x 700 x 860	-16°C ~ -22°C	1 x GN 1/1	3	38°C	SS 304
	CGN 600 C2	2 Door Reach-in Chiller	600	680 x 810 x 2000	-2°C ~ 8°C	2 x GN 1/1	3	43°C	SS 430
	CGN 600 F2	2 Door Reach-in Freezer	600	680 x 810 x 2000	-16°C ~ -22°C	2 x GN 1/1	3	38°C	SS 430
	CGN 600 CF	2 Door Reach-in Combi	300C + 300F	680 x 810 x 2000	-2°C ~ 8°C / -10°C ~ -20°C	2 x GN 1/1	3	38°C	SS 430
	CGN 1200 C4	4 Door Reach-In Chiller	1200	1340 x 810 x 2000	-2°C ~ 8°C	2 x GN 1/1	6	43°C	SS 430
STATIC - CLASSIC	CGN 1200 F4	4 Door Reach-in Freezer	1200	1340 x 810 x 2000	-16°C ~ -22°C	2 x GN 1/1	6	38°C	SS 430
	CGN 2100 C	2 Door Under Counter Chiller	265	1360 x 700 x 860	-2°C ~ 8°C	1 x GN 1/1	2	43°C	SS 430
	CGN 3100 C	3 Door Under Counter Chiller	400	1795 x 700 x 860	-2°C ~ 8°C	1 x GN 1/1	3	43°C	SS 430
	RI 551 C	2 Door Reach-in Chiller	550	680 x 710 x 2000	-2°C ~ 8°C	NA	3	43°C	SS 201
	RI 1101 C	4 Door Reach-in Chiller	1100	1340 x 710 x 2000	-2°C ~ 8°C	NA	6	43°C	SS 201
	RI 551 F	2 Door Reach-in Freezer	550	680 x 710 x 2000	-10°C ~ -20°C	NA	3	43°C	SS 201
	RI 1101 F	4 Door Reach-in Freezer	1100	1340 x 710 x 2000	-10°C ~ -20°C	NA	6	43°C	SS 201
	CGN 1200 CF	4 Door Reach-in Combi	600C + 600F	1340 x 810 x 2000	-2°C ~ 8°C / -10°C ~ -20°C	NA	6	38°C	SS 430
	UC 1501 C	2 Door Undercounter Chiller	265	1360 x 600 x 850	-2°C ~ 8°C	NA	2	38°C	SS 201
	UC 1502 C	2 Door Undercounter Chiller	265	1360 x 700 x 850	-2°C ~ 8°C	NA	2	38°C	SS 201
UC 1801 C	3 Door Undercounter Chiller	400	1795 x 600 x 850	-2°C ~ 8°C	NA	3	38°C	SS 201	
UC 1802 C	3 Door Undercounter Chiller	400	1795 x 700 x 850	-2°C ~ 8°C	NA	3	38°C	SS 201	

Due to continuous product development, specifications, features and colours are subject to change without notice. GN pans are optional and not supplied with the equipment.

\*Selected models.

