



K96L with Milk Cooler & Steamer

Specifications



ITEM	K96L
Voltage/Frequency	220-240V/50-60Hz
Variable brewing chamber	8-14g
Heating Power	2700W
Pre-brew system	Yes
No. of thermoblock heating system	2
No. of Pump	2
Pump Pressure	19 Bar
Water Tank Capacity	6L/Tap Water
Bean Container Capacity	1000g
Capacity of Coffee Ground	30-35 portions
Capacity of Waste Water	2L
Length of Power Cord	1.8m
Height of Coffee Spout	100mm-160mm
N.W/G.W	18.5/23kg
Dimension(D*W*H)	511X403X582mm
Loading Qty. (20ft,40ft)	117/246 units

Milk Cooler



Milk Cooler

Temperature display and controller on canopy, black foam door

Every coffee machine mate is designed to match your coffee machine and fulfill the need of keeping and providing milk.

This unit is suitable for cooling milk, and put this machine beside the coffee machine. Put the milk tube into the milk cooler.

Professional refrigeration ensures the freshness and hygiene. Keep milk freshness and hygiene after open milk cans or bottle.

WPM Steamer

- **MS-130T**
- is WPM first Milk Steamer with Temperature setting.(°C / °F)



Two default temperature buttons

Speed up your setting and suit for your different using purposes.



Short memory function

Record your last temperature set



Clean programs

- Short flushing
- Complete Cleaning



Accurate Design

Frothing fine milk foam without manual control of pitcher