

TRUFROST & BUTLER

Reach in Cabinets - Chillers

These Trufrost Reach-Ins are available as Chillers or Freezers, and come with 2 or 4 door options. Available in a choice of two refrigeration systems - Ventilated or Static with fan, these are offered in capacities ranging from 600 - 1410 litres. There are different models to address the wide-ranging needs right from the professional kitchen of a 5 star hotel to a café or a restaurant.



Available Models

G600TNM, STF600TNM, GN680TNM



Available Models

G1200TNM, STF1200TNM, GN1340TNM, GN1410TNM

Technical Specifications



Product	Model	Dimensions (wxdxh) mm	Internal Dimensions	Volume (L)	Cooling System	Refrigerant	Input Power (W)	Temperature Range (°C)	GN Compatibility	No. of Door/ Drawers	No. of Shelves	Net Weight (Kg)
Reach In Refrigerators	G 600 TNM	680*710*2010	564*582*1394	600	Ventilated	R600a	220	-2 ~ +8	Yes	2	3	115
	STF 600 TNM	680*710*2010	564*582*1394	600	Static with fan	R290	185	-2 ~ +8	-	2	3	115
	GN 680 TNM	680*810*2010	564*682*1394	680	Ventilated	R290	280	-2 ~ +8	GN 2/1	2	3	110
	G 1200 TNM	1340*710*2010	1224*582*1394	1200	Ventilated	R290	400	-2 ~ +8	-	4	6	148
	STF 1200 TNM	1340*710*2010	1224*582*1394	1200	Static with fan	R290	318	-5 ~ +5	-	4	6	148
	GN 1340 TNM	1340*810*2010	1224*682*1394	1340	Ventilated	R290	465	-2 ~ +8	GN 2/1	4	6	167
	GN 1410 TNM	1480*830*2010	1360*630*1400	1410	Ventilated	R290	400	-2 ~ +8	GN 2/1	4	6	172

Electricals: 220V/50Hz/1 Phase

Specifications are subject to change without prior notice due to continuous product development

Contact us : jennifer@trufrost.com

www.trufrost.com