

TRUFROST & BUTLER

Reach in Cabinets - Freezers

These Trufrost Reach-Ins are available as Chillers or Freezers, and come with 2 or 4 door options. Available in a choice of two refrigeration systems - Ventilated or Static with fan, these are offered in capacities ranging from 600 - 1410 litres. There are different models to address the wide-ranging needs right from the professional kitchen of a 5 star hotel to a café or a restaurant.



Available Models

G600BTM, STF600BTM, GN680BTM



Available Models

G1200BTM, STF1200BTM, STF1210DTM, GN1340BTM, GN1410BTM

Technical Specifications



Product	Model	Dimensions (wxdxh) mm	Internal Dimensions	Volume (L)	Cooling System	Refrigerant	Input Power (W)	Temperature Range (°C)	GN Compatibility	No. of Door/ Drawers	No. of Shelves	Net Weight (Kg)
Reach In Freezers	G 600 BTM	680*710*2010	564*582*1394	600	Ventilated	R290	465	-22 ~ -18	-	2	3	126
	STF 600 BTM	680*710*2010	564*582*1394	600	Static with fan	R290	435	-20 ~ -15	-	2	3	155
	GN 680 BTM	680*810*2010	564*682*1394	680	Ventilated	R290	450	-22 ~ -18	GN 2/1	2	3	117
	G 1200 BTM	1340*710*2010	1224*582*1394	1200	Ventilated	R 404a	700	-22 ~ -18	-	4	6	155
	STF 1200 BTM	1340*710*2010	1224*582*1394	1200	Static with fan	R290	626	-20 ~ -15	-	4	6	155
	GN 1340 BTM	1340*810*2010	1224*682*1394	1340	Ventilated	R290	580	-22 ~ -18	GN 2/1	4	6	177
	GN 1410 BTM	1480*830*2010	1360*630*1400	1410	Ventilated	R290	750	-22 ~ -18	GN 2/1	4	6	180

Electricals: 220V/50Hz/1 Phase

Specifications are subject to change without prior notice due to continuous product development

Contact us : jennifer@trufrost.com

www.trufrost.com