

Refrigerated Work Tables- Chillers

Trufrost refrigerated worktables, or refrigerated undercounters as they are also called, combine storage and preparation thereby enhancing the effectiveness of kitchen professionals. They are mounted on heavy duty lockable castors for ease of mobility and cleaning. Available in a choice of two refrigeration systems - Ventilated or Static with fan, these Chillers or Freezers are available in 2 and 3 door options. Options of back splash and a set of 2 or 3 drawers in place of a hinged door are available at an extra cost for project orders.



Available Models

STF 2100 TN (New), STF 2101 TN,
G 2100 TN (New), GN 2100 TN (New)

Available Models

STF 3100TN, STF 3101 TN, STF 3101 TN (New),
G 3100 TN (New), GN 3100 TN (New)

Available Models

S 901

Technical Specifications



Product	Model	Dimensions (WxDxH) mm	Internal Dimensions (WxDxH) mm	Volume (L)	Cooling System	Refrigerant	Input Power (W)	Temperature Range (°C)	GN Compatibility	No. of Door/Drawers	No. of Shelves	Net Weight (Kg)
Undercounter Refrigerators	S 901	903x700x876*	830x595x500	240	Static with fan	R600a	170	2 ~ 10	GN 1/1 Shelf per door	2	2	81
	STF 2100 TN (New)	1200x700x837	800x529x582	270	Static with fan	R134a	300	2 ~ 10	-	2	4	83
	STF 2101 TN	1360x600x850	799x480x564	228	Static with fan	R290	255	2 ~ 10	-	2	2	89
	STF 3100TN	1800x650x800	1380x489x535	430	Static with fan	R134a	180	2 ~ 10	-	3	3	100
	STF 3101 TN	1795x600x850	1234x480x564	339	Static with fan	R290	275	2 ~ 10	-	3	3	111
	STF 3101 TN (New)	1800x700x800	1400x529x582	340	Static with fan	R134a	400	2 ~ 10	-	3	6	107
	G 2100 TN (New)	1360x600x860	902x430x560	228	Ventilated	R600a	275	2 ~ 10	-	2	2	94
	GN 2100 TN (New)	1360x700x860	902x530x560	282	Ventilated	R600a	275	2 ~ 10	GN1/1	2	2	92
	G 3100 TN (New)	1795x600x860	1337x430x560	339	Ventilated	R600a	275	2 ~ 10	-	3	3	127
	GN 3100TN (New)	1795x700x860	1337x530x560	417	Ventilated	R600a	275	2 ~ 10	GN1/1	3	3	114

Electricals: 220V/50Hz/1 Phase

* Height: 976mm with casters

Specifications are subject to change without prior notice due to continuous product development